




PRODUCT DATA SHEET



www.millersoils.co.uk

DATA SHEET 7961

PRODUCT NAME/VISCOSITIES:

CFS 0w20 NT+

DESCRIPTION:

Recommended for modern competition engines where maximum power release is required and beneficial for high revving engines, a lower viscosity oil with extremely high anti wear characteristics it is specifically formulated for use in qualifying or shorter duration events. The fully Synthetic Triple Ester Nano Technology Formulation is for modern competition engines where maximum power release and ultra low friction are required.

APPLICATION:

For competition engines where maximum power release is the preferred criteria, especially for qualifying or shorter duration events where the engine has been designed for this type of crankcase lubricant.

USER BENEFITS:

Fully synthetic Triple Ester Nano Technology Oil provides:

- Laboratory tests and results show up to a further 15% reduction in friction and up to a further 17% reduction in wear over the previous award winning NT range
- Significantly reduced friction
- Reduced component wear promotes longer engine life
- Reduced heat production
- Increased power output and torque
- Improved reliability
- Improved energy efficiency
- Superior anti-friction and anti-wear characteristics


PERFORMANCE PROFILE:

- Manufactured to far exceed the requirements of API SM/CF and ACEA A1/B1
- Formulated for modern high revving engines used in circuit racing or for events such as hill climbs and sprints
- Ideal for use as a qualifying oil
- Suitable for operating at 125°C with peak temperatures up to 150°C





PRODUCT DATA SHEET



www.millersoils.co.uk

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	0w20
Specific Gravity @ 15°C	0.857
Kinematic Viscosity @ 100°C	7.8 cSt
Kinematic Viscosity @ 40°C	42.3cSt
Viscosity Index	157
Pour Point °C	< -48
Flashpoint °C	>200
Cold Crank Viscosity @ -35°C	6,200cP Maximum
TBN mg KOH / gm	10.1

HEALTH AND SAFETY:

Health and Safety Data Sheet 7961 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

