



Product data sheet



PRODUCT NAME/VISCOSITIES:

2 STROKE SELF MIX

DATA SHEET NO: 5107

LM: 13/10/15

DESCRIPTION:

High quality mineral base oils with additives designed specifically for two stroke petrol engines.

APPLICATION:

Dilute with petrol in the ratio prescribed by the equipment manufacturer (petrol/oil ratio) or as received for applications having direct lube injection system.

USER BENEFITS:

The special low ash formulation employed ensures:

- Minimum combustion chamber deposits.
- Reduced pre-ignition and plug fouling.
- Fuel/oil ratio up to 50:1 (check manufacturers recommendation).
- Increased protection from piston seizure and ring sticking.
- Excellent deposit and lacquer control in high temperature areas.
- Reduced port and exhaust system blockage.
- Suitable for lawn mowers, chain saws, portable tools, mopeds, motor cycles and outboard engines not requiring ashless oils.

PERFORMANCE PROFILE:

- Meets the performance requirements of two cycle gasoline engine lubricants for API:TA, TB & TC.

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	40
Sulphated ash %	0.08%
Colour	Blue

HEALTH AND SAFETY:

Health and Safety Data Sheet 5107 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
Visit: millersoils.co.uk