



MILLERS OILS

millersoils.co.uk

PRODUCT DATA SHEET

INDUSTRIAL



**PRODUCT NAME/VISCOSITIES:
90W CYLINDER OIL**

Product No	5080
Issue No.	2
Issue Date	19/02/19

DESCRIPTION:

A heavy viscosity compounded steam cylinder oil with added fatty compounds.

APPLICATION:

Use as received for the lubrication of steam engine cylinders in locomotives and stationary engines working with either superheated or saturated steam.

USER BENEFITS:

- Cylinder Oil lubricants are designed for medium pressure engines and provide:-
- Enhanced lubricating properties.
- High film strength.
- Operation in superheated, dry and wet steam conditions.

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.900
Kinematic Viscosity @ 100°C	72.0cSt
Kinematic Viscosity @ 40°C	1000cSt
Flashpoint °C	260

HEALTH AND SAFETY:

Health and Safety Data Sheet 5080 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

