



**MILLERS OILS**

millersoils.co.uk

**PRODUCT DATA SHEET**  
**INDUSTRIAL**



**INDUSTRIAL**  
  
MILLERS OILS

DATA SHEET NO: 5261

PRODUCT NAME/VISCOSITIES:

**BLACK MOLY MPQ 2**

DESCRIPTION:

A lithium grease with molybdenum disulphide.

APPLICATION:

Use as received for applications throughout industry and the automotive sector.

USER BENEFITS:

- High degree of corrosion protection.
- Excellent pumpability.
- Excellent extreme pressure and anti-wear performance.
- Good performance over a wide temperature range.

TYPICAL CHARACTERISTICS:

Appearance	Grey/Black Smooth Grease
NLGI Classification	2
Thickener	Lithium Soap
Solid Lubricant	Molybdenum Disulphide
Base Oil	Mineral Oil
Base Oil Viscosity @40°C	180cSt
Worked Penetration (IP50)	265 to 295
Drop Point (IP132) °C	185 minimum
Copper Corrosion (IP112)	Pass
Emcor (IP 220) Corrosion Test	0: 0
Four Ball Weld Load (IP239)	315
Timken OK Load (IP326)	23 (50lbs)
Operating Temperature Range °C	-20 to +140

HEALTH AND SAFETY:

Health and Safety Data Sheet 5261 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

Millers Oils Limited  
Brighouse  
West Yorkshire  
HD6 3DP

Tel +44 (0)1484 713201  
Fax +44 (0)1484 721263  
Email [enquiries@millersoils.co.uk](mailto:enquiries@millersoils.co.uk)  
[www.millersoils.co.uk](http://www.millersoils.co.uk)

