



PRODUCT DATA SHEET



Product No	5539
Issue No.	2
Issue Date	24/03/10

PRODUCT NAME/VISCOSITIES: CA HAMMER GREASE

DESCRIPTION:

A soft adhesive semi-synthetic grease produced for the quarry, civil engineering and demolition industries.

APPLICATION:

Use as received for use on contact breaker hammers, hydraulic and air operated hammers, chisels and peckers.

USER BENEFITS:

- Broad operating temperature range in excess of 1,000°C under certain conditions.
- 20% lubricating solids.
- Highly resistant to water.

TYPICAL CHARACTERISTICS:

Appearance	Silver Grey Adhesive Grease
NLGI Classification	2
Thickener	Bentone
Solid Lubricant	Copper, Graphite and Aluminium
Base Oil	Semi-Synthetic
Base Oil Viscosity @40°C	n/a
Worked Penetration (IP50)	n/a
Drop Point (IP132) °C	n/a
Copper Corrosion (IP112)	n/a
Emcor (IP 220) Corrosion Test	n/a
Four Ball Weld Load (IP239)	n/a
Timken OK Load (IP326)	n/a
Operating Temperature Range °C	-20 to + 1,000 under certain conditions

HEALTH AND SAFETY:

Health and Safety Data Sheet 5539 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

