



millersoils.co.uk

PRODUCT DATA SHEET

PREMIUM



DATA SHEET NO: 5777

PRODUCT NAME/VISCOSITIES:

ENGINE FLUSH

DESCRIPTION:

A product to be added to the oil in an engine before a drain and refill is to take place.

APPLICATION:

All car and light van petrol and diesel engines.

Add contents of bottle to oil in the engine – 250ml bottle will treat 4-6 litres of engine oil.

Run engine for 15 to 20 minutes.

Drain the oil, change the oil filter and refill with the recommended grade of Millers engine oil.

USER BENEFITS:

- Ensures engine is clean before new oil is put into engine.

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.845
Kinematic Viscosity @ 100°C	2.5cSt
Kinematic Viscosity @ 40°C	8.0cSt
Pour Point °C	-15
Flashpoint °C	140

HEALTH AND SAFETY:

Health and Safety Data Sheet 5777 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

