



MILLERS OILS

millersoils.co.uk

PRODUCT DATA SHEET

PREMIUM



AUTOMOTIVE



DATA SHEET NO: 7767

PRODUCT NAME/VISCOSITIES:

MILLERMATIC ATF CVT

DESCRIPTION:

Premium fully synthetic automatic transmission fluid.

APPLICATION:

For use in CVT, continuously variable transmissions. Belt, chain and some hybrid systems.

USER BENEFITS:

- The additive selection provides excellent friction durability and anti-shudder performance ensuring smooth transmission of power.
- High resistance to oxidation and degradation providing protection throughout the long service interval.

PERFORMANCE PROFILE:

Suitable for use where the following specifications are called for by the vehicle manufacturer:-

- Audi/VW TL 52180, G 052 180
- Dodge/Jeep NS-2, CVT+4
- Ford CVT23, CVT30/Mercon C
- GM/Saturn DEX-CVT
- Honda HMMF, HCF-2
- Hyundai CVTF
- Hyundai/Kia SP-III
- MB 236.20
- Mini Cooper EZL 799
- Mitsubishi CVTF-J1/SP-III
- Nissan NS-2
- Subaru NS-2/Lineartronic CVTF
- Suzuki TC/NS-2/CVT
- Toyota TC
- Toyota T-III

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.855
Kinematic Viscosity @ 100°C	7.45cSt
Kinematic Viscosity @ 40°C	35.7 cSt
VI	182
Pour Point °C	-47
Flashpoint °C	226

Millers Oils Limited
Brighthouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk





MILLERS OILS

millersoils.co.uk

PRODUCT DATA SHEET

PREMIUM



AUTOMOTIVE



Brookfield Viscosity@-40°C

11,200 cP

HEALTH AND SAFETY:

Health and Safety Data Sheet 7767 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

