



MILLERS OILS

millersoils.co.uk

PRODUCT DATA SHEET

PREMIUM



AUTOMOTIVE



DATA SHEET NO: 6213

PRODUCT NAME/VISCOSITIES:

MILLERMATIC ATF SPIII-WS

DESCRIPTION:

Premium fully synthetic automatic transmission fluid.

APPLICATION:

An automatic transmission fluid formulated to meet the high performance levels required by Japanese and Korean manufacturers.

USER BENEFITS:

- The additive selection provides excellent friction durability and anti-shudder performance. Ensuring a smooth transmission of power
- High resistance to oxidation and degradation, providing protection throughout the long service intervals
- Also suitable for SP-IV applications

PERFORMANCE PROFILE:

Suitable for use where the following specifications are called for by the vehicle manufacturer:-

OEM Group	Specification
Acura	ATF-Z1
Audi (VAG)	G 055 005 A1 / A2 / A6, G 055 025 A2, G 052 162 A1 / A2 / A6, G 052 990, G 055 540
Bentley	PY112995PA
BMW	ETL7045E, ETL80728
Chrysler	MS7176E, MS9602, ATF+, ATF+2, ATF+3, ATF+4, Mopar AS 68 RC, 05127382AA
Daimler	ATF+3, ATF+4
Fiat	9.55550-AV1, 9.55550-AV2, 9.55550-AV4
Ford	Mercon, Mercon V, Mercon SP, M2C992A1, 924A, M2C138CJ, M2C166H, RNR5
General Motors	GM Dexron III, GM 9986195, GM 88863400, GM 88863401, GM 93160393
Honda	ATF Z1 (Except CVT's), ATF DW-1
Hyundai	SP II, SP III, SP IV, SP IV M, SP IV-RR, JWS 3314, NWS 9638, 040000C90SG
Infiniti	MATIC C, MATIC D, MATIC J, MATIC K, MATIC S
Isuzu	SCS fluid, BESCO ATF II, ATF III, ATF SP
Jaguar	Jaguar Fluid 8432, JLM20238, ATF 3403 M115,
Kia	Red 1, SP-II, SP-III, SP-IV, SP-IVM
Land Rover	TYK5000050

Millers Oils Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk





MILLERS OILS

millersoils.co.uk

PRODUCT DATA SHEET

PREMIUM



AUTOMOTIVE



DATA SHEET NO: 6213

Lexus	JWS3309
Maserati	231603
Mazda	ATF D-II , M-III , M-V , FZ , F-1 , S-1 , N-1 , ATF 3317
Mini	T-IV
Mitsubishi	Diaqueen ATF PA , ATF AW , ATF J2 , ATF J3 , Diaqueen SK , SP-II , SP-III
Nissan	MATIC C , MATIC D , MATIC J , MATIC K , MATIC S
Porsche	ATF 3403-M115 , T-IV
Saab	JWS3309 , 93 165 147
Subaru	Subaru ATF , K0140Y0700 , ATF SAT , ATF , ATF HP
Suzuki	ATF AW-1 , 5D06 , ATF 2326 , ATF 2384K , JWS3309 , ATF 3314 , ATF 3317
Toyota	ATF D-II , ATF D-III , ATF T-III , ATF T-IV
Volvo	97325 , 97335 , CE 97340 , 1161540-S
VW (VAG)	G 055 005 A1 / A2 / A6 , G 055 025 A2 , G 052 162 A1 / A2 / A6 , G 052 990 , G 055 540

STANDARDS

Aisin Warner	JWS 3309 , JWS3324
Allison	C-3 & C-4
ZF	TE-ML 05L , 09 , 21L

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.848
Kinematic Viscosity @ 100°C	7.4cSt
Kinematic Viscosity @ 40°C	35.0cSt
Viscosity Index	185
Pour Point °C	-42
Flashpoint °C	200
Colour	Red

HEALTH AND SAFETY:

Health and Safety Data Sheet 6213 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

