



millersoils.co.uk

PRODUCT DATA SHEET
PREMIUM



AUTOMOTIVE



DATA SHEET NO: 5619

PRODUCT NAME/VISCOSITIES:

STOP LEAK

DESCRIPTION:

A product to be added to the oil in an engine or gearbox to help minimise leaks.

APPLICATION:

For use in all car and light van petrol and diesel engines gearboxes and axles.
Add contents of bottle to oil in the engine gearbox or differential.

USER BENEFITS:

- Helps maintain oil tightness of old or leaky seals.
- Effectively minimises the risk of leaks.

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	10
Specific Gravity @ 15°C	0.870
Kinematic Viscosity @ 100°C	5.5cSt
Kinematic Viscosity @ 40°C	30.5cSt
Viscosity Index	112
Pour Point °C	<-10
Flashpoint °C	>200

HEALTH AND SAFETY:

Health and Safety Data Sheet 5405 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

