



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES: TRX SEMI SYNTHETIC 75w90

Product No	5522
Issue No.	2
Issue Date	17/09/13

DESCRIPTION:

A semi synthetic transmission oil incorporating extreme pressure (EP) additives.

APPLICATION:

For use in cars and light van manual gearboxes and axles where an API GL-4/GL-5 specification of gear oil is required.

USER BENEFITS:

- TRX 75w90 provides full protection against wear and corrosion
- It improves the quality and "feel" of the gear change
- It can be used to top up gearboxes and will mix safely with other oils except ATFs

PERFORMANCE PROFILE:

- API GL-4 [EP]
- API GL-5 [Hypoid]

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	75w90
Specific Gravity @ 15°C	0.879
Kinematic Viscosity @ 100°C	13.72cSt
Kinematic Viscosity @ 40°C	92.1cSt
Viscosity Index	151
Brookfield Viscosity @ -40°C	122,000 cP
Pour Point °C	-40
Flashpoint °C	200

HEALTH AND SAFETY:

Health and Safety Data Sheet 5522 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk