



Product data sheet



Product No.	5991
Issue No.	1
Issue Date	23/2/2018

PRODUCT NAME/VISCOSITIES:

Trident 10w40

DESCRIPTION:

Trident 10w40 semi synthetic full SAPS (Sulphated Ash, Phosphorous & Sulphur) engine oil is suitable for the latest engine technology. Designed to meet OEM (Original Equipment Manufacturer) specifications and offer increased cleanliness and engine/oil durability. Trident 10w40 is recommended for engines requiring an SAE 10w40 viscosity meeting the below manufacturer specifications.

USER BENEFITS:

- This synthetic technology produces excellent low temperature flow when cold starting down to -25°C, this yields rapid protection of vital components, as most engine wear occurs during start up.
- Trident 10w40 offers viscosity stability at high temperatures and severe operating conditions for maintainable protection and prolonged engine life.
- Increased protection via a stronger oil film between metallic components.
- Low viscosity offers improved fuel economy in comparison to thicker viscosity oils. Trident 10w40 uses optimum levels of detergents and dispersants. These provide high levels of engine cleanliness and sludge control, which offers improved combustion.
- ACEA Full SAPS specification.



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
Visit: millersoils.co.uk



MILLERS OILS

Product data sheet



PERFORMANCE PROFILE:

- ACEA A3/B3, A3/B4
- API SL,CF
- MB 229.1

Also suitable for:

- Fiat 9.55535-G2
- MB 229.3
- MTF-94 Gear Oil Specification
- PSA B71 2291
- PSA B71 2295
- PSA B71 2300
- Renault RN0700
- VW 500.00/501.01
- VW 502.00/505.00

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	10w40
Specific Gravity @ 1°C	0.872
Kinematic Viscosity @ 100° C	14.1cSt
Kinematic Viscosity @ 40°C	96.7cSt
Viscosity Index	149
Pour point °C	<-42
Flashpoint °C	>200
Cold Crank Viscosity @ -25°C	7,000cP max

HEALTH AND SAFETY:

When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
Visit: millersoils.co.uk