



Product data sheet



Product No.	7625
Issue No.	1
Issue Date	23/02/2018

PRODUCT NAME/VISCOSITIES:

TRIDENT 5w40

DESCRIPTION:

Trident 5w40 fully synthetic full SAPS (Sulphated Ash, Phosphorous & Sulphur) engine oil is suitable for the latest engine technology. Designed to meet OEM (Original Equipment Manufacturer) specifications and offer increased cleanliness and engine/oil durability. Trident 5w40 is recommended for engines requiring an SAE 5w40 viscosity meeting the below manufacturer specifications.

USER BENEFITS:

- This synthetic technology produces excellent low temperature flow when cold starting down to -30°C , this yields rapid protection of vital components, as most engine wear occurs during start up.
- Trident 5w40 offers viscosity stability at high temperatures and severe operating conditions for maintainable protection and prolonged engine life.
- Increased protection via a stronger oil film between metallic components.
- Low viscosity offers improved fuel economy in comparison to thicker viscosity oils. Trident 5w40 uses optimum levels of detergents and dispersants. These provide high levels of engine cleanliness and sludge control, which offers improved combustion.
- ACEA Full SAPS specification.

PERFORMANCE PROFILE:

- ACEA A3 /B3, A3/B4
- API SL,CF
- MB 229.1



Millers Oils Ltd
 Brighouse, West Yorkshire
 HD6 3DP, UK
 Tel: +44(0)1484 713201
 Visit: millersoils.co.uk



MILLERS OILS

Product data sheet



Also suitable for:

- BMW Longlife-98
- BMW Longlife-01
- Chrysler MS 12991
- Fiat 9.55535.M2
- Fiat 9.55535.N2
- Fiat 9.55535.Z2
- GM-LL-A-025
- GM-LL-B-025
- MB 229.3
- MB 229.5
- PSA B71 2293
- PSA B71 2296
- Renault RN0700
- Renault RN0710
- VW 502.00/505.00

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	5w40
Specific Gravity @ 15°C	0.857
Kinematic Viscosity @ 100°C	12.79cSt
Kinematic Viscosity @ 40°C	77.7cSt
Viscosity Index	165
Pour point °C	<-30
Flashpoint °C	>200
Cold Crank Viscosity @ -30°C	6,600cP max

HEALTH AND SAFETY:

When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
Visit: millersoils.co.uk