



Product data sheet



Product No.	8058
Issue no.	1
Issue date	23/2/2018

PRODUCT NAME/VISCOSITIES:

TRIDENT LONGLIFE FUEL ECONOMY 5w30

DESCRIPTION:

Trident Longlife Fuel Economy 5w30 is a high performance fully synthetic Full SAPS (Sulphated Ash, Phosphorous & Sulphur) engine oil suitable for the latest engine technology. It has been designed to meet OEM (Original Equipment Manufacturer) specifications, which has been achieved by offering increased cleanliness, engine/oil durability, reduced friction/wear and improved fuel economy.

Trident Longlife Fuel Economy 5w30 is recommended for engines requiring an SAE 5w30 viscosity predominantly Ford and Jaguar Land Rover vehicles. Trident Longlife Fuel Economy 5w30 is fully compatible with the latest European emissions standards.

USER BENEFITS:

- This synthetic technology produces excellent low temperature flow when cold starting down to -30°C, this yields rapid protection of vital components, as most engine wear occurs during start up.
- It offers exceptional viscosity stability at high temperatures and severe operating conditions for maintainable protection and prolonged engine life.
- Increased protection via a stronger oil film between metallic components, with an achievable level of performance throughout the OEM oil change interval.
- Low viscosity offers improved fuel economy in comparison to thicker viscosity oils. Trident 5w30 uses optimum levels of detergents and dispersants. These provide high levels of engine cleanliness and sludge control, which offers improved combustion.
- ACEA Full SAPS specification.



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
Visit: millersoils.co.uk



MILLERS OILS

Product data sheet



PERFORMANCE PROFILE:

- ACEA A5/B5
- API SL.CF
- Ford M2C913-B
- Ford M2C913-C
- Ford M2C913-D
- Jaguar Land Rover STJLR.03.5003
- Renault RN0700

Also suitable for:

- Chrysler MS 6395
- Ford M2C912-A1
- Ford M2C913-A
- Ford M2C929-A
- Ford M2C930-A
- ILSAC GF-4

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	5w30
Specific Gravity @ 15°C	0.851
Kinematic Viscosity @ 100°C	9.8cSt
Kinematic Viscosity @ 40°C	54.6cSt
Viscosity Index	167
Pour Point °C	-46
Flashpoint °C	>200
Cold Crank Viscosity @ -30°C	6,600cP max

HEALTH AND SAFETY:

When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
Visit: millersoils.co.uk