



millersoils.co.uk

PRODUCT DATA SHEET  
**COMMERCIAL**  
VEHICLE



DATA SHEET NO: 7727

PRODUCT NAME/VISCOSITIES:

**TRUCKMASTER EE 15w40**

DESCRIPTION:

A high quality, low friction, fuel efficient engine oil. Part of the Millers Oils NANODRIVE Low Friction Technology range. Formulated to meet the requirements of Volvo VDS-3, MB 228.3, Cummins 20078, ACEA E7 and API CI-4 specification long drain diesel engines with the added benefits of reduced friction, improved fuel economy and a reduction in overall running costs.

APPLICATION:

Truckmaster EE 15w40 is especially suitable where long and extended oil drain intervals are required as part of the vehicle maintenance scheduling. The Millers Oils NANODRIVE Low Friction Technology adds further economical benefits. It is often used in conjunction with the Millers Oils Oil Analysis System to monitor oil condition throughout the drain interval.

FEATURES AND BENEFITS:

The Millers Oils NANODRIVE Low Friction Technology provides the following benefits:

- A reduction in friction of up to 59% providing a reduction in wear of 8% compared to other standard E7 15w40 grades.
- The coefficient of friction reduces rapidly as the engine temperature rises, maximising fuel economy, and reduces emissions accordingly.
- Protects against wear, extending engine component life.
- Overall running costs are reduced through lower fuel consumption and longer component life.
- The combination of premium grade base oils, viscosity index improvers and the performance additive package has provided an engine oil of outstanding capability.

SPECIFICATIONS:

- ACEA E7, A3/B4
- API CI-4 /SL
- MB 228.3/ 229.1
- Volvo VDS-3
- Renault RVI RLD2
- MTU Category 2

- Cummins 20071, 2, 6, 7, 8
- Mack EO-N, EO-M Plus
- MAN M3275
- CAT ECF-2
- Global DHD-1
- Deutz DQC 111-10

Millers Oils Limited  
Brighouse  
West Yorkshire  
HD6 3DP

Tel +44 (0)1484 713201  
Fax +44 (0)1484 721263  
Email [enquiries@millersoils.co.uk](mailto:enquiries@millersoils.co.uk)  
[www.millersoils.co.uk](http://www.millersoils.co.uk)





**MILLERS OILS**

millersoils.co.uk

**PRODUCT DATA SHEET**  
**COMMERCIAL**  
**VEHICLE**



COMMERCIAL VEHICLE



**TYPICAL CHARACTERISTICS:**

SAE Viscosity Grade	15w40
Specific Gravity @ 15°C	0.889
Kinematic Viscosity @ 100°C	14.27cSt
Kinematic Viscosity @ 40°C	103.36cSt
Viscosity Index	141
Pour Point °C	<-20
Flashpoint °C	>200
Cold Crank Viscosity @ -20°C	7,000cP max
TBN mg KOH/gm	11.71
Sulphated ash %	1.49

**STORAGE:**

All packages should be stored indoors at ambient temperatures in a well-ventilated area. Keep containers tightly closed when not in use. Where storing outside is unavoidable, barrels should be laid horizontally to avoid water ingress and to protect the product labelling and marking. Clean up any spilled material immediately. Take all necessary precautions against accidental spillage into soil or water.

**HEALTH AND SAFETY AND ENVIRONMENT:**

Health and Safety and Environment information is provided for this product in Millers Oils Material Safety Data Sheet 7727. This gives details of any potential hazards, necessary precautions, first aid measures, environmental effects and disposal procedures.

All information relates only to the specific products designated herewith and may not be valid for this material if used in conjunction with any other materials or in any other process.

For Technical assistance call +44 (0) 1484 475060 or email [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

Millers Oils Limited  
Brighouse  
West Yorkshire  
HD6 3DP

Tel +44 (0)1484 713201  
Fax +44 (0)1484 721263  
Email [enquiries@millersoils.co.uk](mailto:enquiries@millersoils.co.uk)  
[www.millersoils.co.uk](http://www.millersoils.co.uk)

