



PRODUCT DATA SHEET



Product No	7950
Issue No.	1
Issue Date	18/10/2016

PRODUCT NAME/VISCOSITIES:

XF LONGLIFE 0w20

DESCRIPTION:

A high performance fully synthetic fuel efficient engine oil for makes such as Chrysler, Honda, Lexus, Mazda, Mitsubishi, Nissan, Proton, Subaru, Suzuki and Toyota.

APPLICATION:

Synthetic engine oil technology for passenger car gasoline engines which provides protection from deposits and wear. Not recommended for cars requiring low or mid saps.

USER BENEFITS:

- Improved engine efficiency and improves fuel economy
- Excellent low temperature performance
- Excellent oxidation and thermal stability
- Wear protection throughout the drain period

PERFORMANCE PROFILE:

- ILSAC GF-5
- API SN

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	0w20
Specific Gravity @ 15°C	0.846
Kinematic Viscosity @ 100°C	7.77cSt
Kinematic Viscosity @ 40°C	43.8cSt
Viscosity Index	148
Pour Point °C	-39
Flashpoint °C	>200
Cold Crank Viscosity @-30°C	6,200cP max

HEALTH AND SAFETY:

Health and Safety Data Sheet 7950 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

