



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES:

XF LONGLIFE 0w30

Product No	7858
Issue No.	2
Issue Date	09/01/2015

DESCRIPTION:

A high performance fully synthetic fuel efficient engine oil suitable for the latest Volvo petrol and diesel engine vehicles.

APPLICATION:

Produced for the very latest Volvo petrol and diesel engines. Also, listed by Dacia, Honda, Mazda, Mitsubishi and certain Renault models.

USER BENEFITS:

- The high quality of this oil means that fuel economy is maximised at the same time as engine wear is being minimised.
- Oil viscosity or thickness is maintained even under the most severe operating conditions thereby ensuring maximum engine protection.
- Formulated to meet the Volvo requirement for improved fuel economy.

PERFORMANCE PROFILE:

- ACEA A5 / B5
- API SL, CF
- Meets the requirements of Volvo VCC 95200377

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	0w30
Specific Gravity @ 15°C	0.849
Kinematic Viscosity @ 100°C	10.19cSt
Kinematic Viscosity @ 40°C	52.93cSt
Viscosity Index	185
Pour Point °C	-50
Flashpoint °C	224
Cold Crank Viscosity @ -35°C	5,820cP

HEALTH AND SAFETY:

Health and Safety Data Sheet 7858 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

