



# PRODUCT DATA SHEET



Product No	7640
Issue No.	1
Issue Date	02/06/2015

## PRODUCT NAME/VISCOSITIES:

### XF LONGLIFE 5w40

#### DESCRIPTION:

A high performance fully synthetic petrol and diesel engine oil. Suitable for use in a range of applications including PD, VW 'Pumpe Düse' engines.

#### APPLICATION:

Suitable for use in petrol and diesel engines meeting the latest European emissions standards, with or without diesel particulate filters including VW 'Pumpe Düse' engine fitted to many Volkswagen/Audi Group and some Ford vehicles.

Particularly recommended for use in vehicles using variable service intervals and other vehicles that require a fuel-efficient lubricant.

#### USER BENEFITS:

- The high quality of this oil means that fuel economy is maximised at the same time as engine wear is being minimised. Oil viscosity or thickness is maintained even under the most severe of operating conditions thereby ensuring maximum engine protection
- A mid SAPS formulation which is compatible with catalysts and diesel particulate filters (DPFs)
- A single 5w40 oil covering many OEM performance profiles

#### PERFORMANCE PROFILE:

- ACEA C3
- API SN, CF
- Meets the requirements of MB 229.31, MB 229.51
- VW 502 00, 505 01
- Ford M2C917-A
- BMW Longlife-04
- Porsche A40 (approval)
- GM dexos 2
- Fiat 9.55535-S2





# PRODUCT DATA SHEET



## TYPICAL CHARACTERISTICS:

SAE Grade	SAE 5w40
Specific Gravity @ 15°C	0.848
Kinematic Viscosity @ 100°C	13.9cSt
Kinematic Viscosity @ 40°C	82.6cSt
Viscosity Index	173
Pour point °C	-39
Flashpoint °C	>200
Cold Crank Viscosity @ -30°C	6,600Cp max

## HEALTH AND SAFETY:

Health and Safety Data Sheet 7640 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

