



PRODUCT DATA SHEET



Product No	7997
Issue No.	1
Issue Date	31/05/2017

PRODUCT NAME/VISCOSITIES: XF LONGLIFE C2 0w30

DESCRIPTION:

A high performance fully synthetic mid SAPS (Sulphated Ash, Phosphorous, Sulphur) engine oil suitable for the latest petrol and diesel engine technology.

APPLICATION:

Suitable for use in petrol and diesel engines meeting Euro IV/V/VI emission standard requiring ACEA C2 specification.

Manufacturer requirement for many Peugeot, Toyota and Citroen vehicles, and preferred grade for many other manufacturers such as Hyundai, Honda, Chevrolet, Kia, Lexus, Mitsubishi, Subaru and Suzuki models.

USER BENEFITS:

- The high quality of this oil means that fuel economy is maximised at the same time as engine wear is being minimised. Oil viscosity or thickness is maintained even under the most severe of operating conditions thereby ensuring maximum engine protection.
- A mid SAPS formulation which is compatible with catalysts and diesel particulate filters (DPFs)

PERFORMANCE PROFILE:

- ACEA C2
- API SN, CF
- PSA B71 2312
- Fiat 9.55535-GS1, 9.55535-DS1
- BMW Longlife 12FE

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	0w30
Specific Gravity @ 15°C g/ml	0.842
Kinematic Viscosity @ 100°C cSt	9.7
Kinematic Viscosity @ 40°C cSt	52.5
Viscosity Index	173
Pour Point °C	-51
Flashpoint °C	>200
Cold Crank Viscosity @ -35°C cP	5954

HEALTH AND SAFETY:



PC & LCV



PRODUCT DATA SHEET



Health and Safety Data Sheet 7997 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk