



# PRODUCT DATA SHEET



Product No	6229
Issue No.	1
Issue Date	22/12/2014

## PRODUCT NAME/VISCOSITIES: XF LONGLIFE C2 5w30

### DESCRIPTION:

A high performance fully synthetic mid SAPS (Sulphated Ash, Phosphorous, Sulphur) engine oil suitable for the latest petrol and diesel engine technology.

### APPLICATION:

Suitable for use in petrol and diesel engines meeting the latest European emission standards requiring ACEA C2 specification.

Manufacturer requirement for many Peugeot, Citroen and Renault vehicles, and preferred grade for many other manufacturers such as Fiat, Alfa Romeo, Chevrolet, Lancia, Lexus and Toyota.

### USER BENEFITS:

- The high quality of this oil means that fuel economy is maximised at the same time as engine wear is being minimised. Oil viscosity or thickness is maintained even under the most severe of operating conditions thereby ensuring maximum engine protection.
- A mid SAPS formulation which is compatible with catalysts and diesel particulate filters (DPFs)

### PERFORMANCE PROFILE:

- ACEA C2
- API SN, CF
- Meets the requirements of PSA B71 2290
- Fiat 9.55535-S1

### TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	5w30
Specific Gravity @ 15°C	0.846
Kinematic Viscosity @ 100°C	10.3cSt
Kinematic Viscosity @ 40°C	57.2cSt
Viscosity Index	171
Pour Point °C	<-35
Flashpoint °C	>200
Cold Crank Viscosity @ -35°C	6,600cP max



PC & LCV



# PRODUCT DATA SHEET



## HEALTH AND SAFETY:

Health and Safety Data Sheet 6229 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)



**Millers Oils Ltd**  
Brighouse, West Yorkshire  
HD6 3DP, UK  
**Tel: +44(0)1484 713201**  
**[www.millersoils.co.uk](http://www.millersoils.co.uk)**