



# PRODUCT DATA SHEET



Product No	7998
Issue No.	1
Issue Date	16/01/2017

## PRODUCT NAME/VISCOSITIES: XF LONGLIFE C3 0w30

### DESCRIPTION:

A high performance fully synthetic mid SAPS (Sulphated Ash, Phosphorous, Sulphur) engine oil suitable for the latest technology petrol and diesel engines.

### APPLICATION:

Suitable for use in petrol and diesel engines meeting Euro IV/V/VI emissions standards requiring ACEA C3 specification.

Particularly recommended by Mercedes-Benz and BMW for use with variable service intervals and other vehicles such as Honda, Hyundai, Kia, Mazda, MG, Mitsubishi and Subaru that require a fuel-efficient lubricant.

### USER BENEFITS:

- The high quality of this full synthetic oil means that fuel economy is maximised at the same time as engine wear is being minimised.
- Oil viscosity or thickness is maintained even under the most severe operating conditions thereby ensuring maximum engine protection.

### PERFORMANCE PROFILE:

- ACEA C3
- API SN, CF
- BMW Longlife-04
- Mercedes-Benz 229.51
- GM dexos 2

### TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	0w30
Specific Gravity @ 15°C g/ml	0.845
Kinematic Viscosity @ 100°C cSt	12.0
Kinematic Viscosity @ 40°C cSt	67.0
Viscosity Index	178
Pour point °C	-51
Flashpoint °C	>200
Cold Crank Viscosity @ -30°C cP	5876





# PRODUCT DATA SHEET



## HEALTH AND SAFETY:

Health and Safety Data Sheet 7998 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

