



PRODUCT DATA SHEET



Product No	6230
Issue No.	1
Issue Date	15/07/2015

PRODUCT NAME/VISCOSITIES: **XF LONGLIFE C3 5w30**

DESCRIPTION:

A high performance fully synthetic mid SAPS (Sulphated Ash, Phosphorous, Sulphur) engine oil suitable for the latest technology petrol and diesel engines.

APPLICATION:

Suitable for use in petrol and diesel engines meeting the European emissions standards requiring ACEA C3 specification.

Particularly recommended by Mercedes-Benz and BMW for use with variable service intervals and other vehicles that require a fuel-efficient lubricant.

USER BENEFITS:

- The high quality of this full synthetic oil means that fuel economy is maximised at the same time as engine wear is being minimised.
- Oil viscosity or thickness is maintained even under the most severe operating conditions thereby ensuring maximum engine protection.

PERFORMANCE PROFILE:

- ACEA C3
- API SN, CF
- Meets the requirements of BMW Longlife-04
- Mercedes-Benz 229.51 (Approval)
- GM dexos 2
- VW 502.00 , 505.01
- Fiat 9.55535-S3

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	5w30
Specific Gravity @ 15°C	0.849
Kinematic Viscosity @ 100°C	12.1cSt
Kinematic Viscosity @ 40°C	72.1cSt
Viscosity Index	165
Pour point °C	-45
Flashpoint °C	>200
Cold Crank Viscosity @ -30°C	6,600cP max





PRODUCT DATA SHEET



HEALTH AND SAFETY:

Health and Safety Data Sheet 6230 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk