



Product data sheet



Product No	7779
Issue No.	1
Issue Date	06/01/2015

PRODUCT NAME/VISCOSITIES:

XF LONGLIFE EB 5w20

DESCRIPTION:

A high performance fully synthetic fuel efficient engine oil to the Ford WSS-M2C948-B specification.

APPLICATION:

Initially introduced for the Ford 1.0L 3 cylinder EcoBoost petrol engine providing improved fuel economy of 1.1% compared to using a WSS-M2C913-C oil. Is fully compatible and recommended for use in petrol engines for which the WSS-M2C913-B, 913-C and WSS-M2C925-B was recommended (with a few exclusions including Ford Ka, Focus ST and RS.)

USER BENEFITS:

- Improved fuel economy
- Excellent low temperature performance
- Excellent oxidation and thermal stability
- Wear protection throughout the drain period

PERFORMANCE PROFILE:

- ACEA A1/B1
- API SN, CF
- Meets the requirements of Ford WSS-M2C948-B

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	5w20
Specific Gravity @ 15°C	0.849
Kinematic Viscosity @ 100°C	7.85cSt
Kinematic Viscosity @ 40°C	44.37cSt
Viscosity Index	148
Pour Point °C	-39
Flashpoint °C	>200
Cold Crank Viscosity @ -30°C	6,600cP max



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
Visit: millersoils.co.uk



Product data sheet



HEALTH AND SAFETY:

Health and Safety Data Sheet 7779 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
Visit: millersoils.co.uk