



Product data sheet



Product No	6221
Issue No.	1
Issue Date	16/11/2015

PRODUCT NAME/VISCOSITIES: XF LONGLIFE ECO 5w30

DESCRIPTION:

A high performance fully synthetic fuel efficient engine oil suitable for the latest technology petrol and diesel engines.

APPLICATION:

Suitable for use in the very latest Ford petrol and diesel engines meeting the latest European emissions standards.

USER BENEFITS:

- The high quality of this oil means that fuel economy is maximised at the same time as engine wear is being minimised.
- Oil viscosity or thickness is maintained even under the most severe operating conditions thereby ensuring maximum engine protection.
- Formulated to meet the Ford requirement for improved fuel economy.
- Backwards compatible with previous M2C913-B and C specification.

PERFORMANCE PROFILE:

- ACEA A5 / B5
- API SL, CF
- Meets the requirements of Ford M2C913-D, M2C913-C, M2C913-B
- Renault RN0700
- Jaguar Land Rover STJLR 03.5003

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	5w30
Specific Gravity @ 15°C	0.850
Kinematic Viscosity @ 100°C	9.7cSt
Kinematic Viscosity @ 40°C	54.0cSt
Viscosity Index	167
Pour Point °C	-45
Flashpoint °C	>200
Cold Crank Viscosity @ -30°C	6,600cP max



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
Visit: millersoils.co.uk



MILLERS OILS

Product data sheet

**HEALTH AND SAFETY:**

Health and Safety Data Sheet 6221 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
Visit: millersoils.co.uk