



# PRODUCT DATA SHEET



Product No	5405
Issue No.	1
Issue Date	27/04/2015

## PRODUCT NAME/VISCOSITIES:

### XFE 10w40

#### DESCRIPTION:

A high quality semi synthetic engine oil of SAE 10w40 viscosity.

#### APPLICATION:

Recommended for use in diesel and petrol engines fitted to cars and light vans. Suitable for both turbo charged and non-turbo engines.

#### USER BENEFITS:

- Will allow fuel economy and engine performance to be maximised.
- Enhanced protection is provided against wear and corrosion.
- XFE is formulated to minimise deposits and maintain a high level of engine cleanliness.

#### PERFORMANCE PROFILE:

- ACEA A3 / B4
- API SL, CF
- Meets the requirements of MB 229.1
- VW 502 00, 505 00
- Renault RN0700
- PSA B71 2294

#### TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	10w40
Specific Gravity @ 15°C	0.872
Kinematic Viscosity @ 100°C	13.7cSt
Kinematic Viscosity @ 40°C	89.7cSt
Viscosity Index	155
Pour Point °C	<-25
Flashpoint °C	>200
Cold Crank Viscosity @ -25°C	7,000Cp max

#### HEALTH AND SAFETY:

Health and Safety Data Sheet 5405 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)



**Millers Oils Ltd**  
Brighouse, West Yorkshire  
HD6 3DP, UK  
Tel: +44(0)1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)