

TECHNICAL DATA SHEET



Product code: 5277

Sector: Industrial

Issue No: 3

Issue Date: 28/10/24

DELTA 3EP

A premium quality lithium grease with extreme pressure (EP) performance.

Application

Suitable for all anti-friction and plain bearings subjected to high shock and vibration conditions for applications throughout industry and the automotive sectors.

Features & Benefits

- Extreme pressure (EP) performance.
- Good pumpability.
- High degree of corrosion protection.
- Multi purpose grease particulars for heavy duty applications.

Typical Characteristics

Appearance	Smooth Brown Grease
NLGI Classification	3
Thickener	Lithium Soap
Solid Lubricant	n/a
Base Oil	Mineral Oil
Base Oil Viscosity @40°C	180cSt
Worked Penetration (IP50)	220 to 250
Drop Point (IP132) °C	185 minimum
Copper Corrosion (IP112)	Pass
Emcor (IP 220) Corrosion Test	00:00
Four Ball Weld Load (IP239)	315kgs
Timken OK Load (IP326)	23kgs (50lbs)
Operating Temperature Range °C	-20 to +140

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk