

Product code: 5857

Sector: Industrial

Issue No: 1

Issue Date: 20/10/25

Millmax ZF 100

Millmax ZF 100 is a premium anti-wear hydraulic oil, specifically engineered to excel in heavy loaded hydraulic systems, ensuring smooth and efficient equipment operation. Surpassing industry standards such as DIN 51524-2 and ISO 11158, Millmax ZF 100 provides superior protection and helps prevent downtime.

Application

Suitable for use in heavy loaded industrial machines, including systems containing gears and bearings that require an ISO VG 100 HLP.

Features & Benefits

- Exceptional resistance to compression ensures efficient power transfer.
- Zinc-free anti-wear properties protect components, extending equipment lifespan.
- Superior thermal and oxidation stability maintains system cleanliness over time.
- Low-foaming formula minimises aeration and cavitation, ensuring consistent power transfer.
- Demulsification prevents water contamination, reducing the risk of rust, corrosion, and decreased lubricity.
- Compatible with elastomers and seals, enhancing seal life and reducing maintenance requirements.

Performance Profile

- DIN 51524-2 (HLP)
- ISO 11158 (HM)
- ASTM D6158
- SAE MS 1004

Typical Characteristics

Density @ 15°C, g/ml	0.879
KV @ 40°C, cSt	99.6
KV @ 100°C, cSt	11.5
Viscosity Index	103
Pour point, °C	≥-20°C
Flash point, °C	≥220°C

TECHNICAL DATA SHEET



Millers Oils Ltd
Brighouse, West Yorkshire, HD6 3DP, UK
T: +44 (0)1484 713201

www.millersoils.co.uk

Technical Support
T: +44 (0)1484 475060
E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website

ADVANCED OILS,
LUBRICANTS & TREATMENTS
SINCE 1887