

TECHNICAL DATA SHEET



Product code: 7875

Sector: Industrial

Issue No: 2

Issue Date: 16/05/22

MILLERGREASE SYNTH HT 2

A premium quality lithium complex grease reinforced with Extreme Pressure (EP) anti-corrosion additives and PTFE.

Application

Designed for use in anti-friction and plain bearings subjected to high temperatures over extended periods without leaving dry residues associated with conventional greases.

Features & Benefits

- Excellent high temperature capability, reducing carbon residues and extending the lubrication intervals.
- Also provides excellent lubrication at sub-zero temperatures.
- Extreme pressure additives and PTFE extend component life.
- Excellent corrosion protection of components and working surfaces.

Typical Characteristics

Appearance	Brown Smooth Grease
NLGI Classification	2
Thickener	Lithium Complex
Base Oil	Synthetic
Worked Penetration (IP50)	265-295
Drop Point (IP132) °C	250 minimum
Copper Corrosion (IP 112)	Pass
Emcor (IP 220) Corrosion Test	00:00
Water Washout @ 39°C % (ASTM D1264)	3
Four Ball Weld Load (IP239)	355kgs
Operating Temperature Range °C	-50 to +220
Solids %	1

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk



MADE IN BRITAIN

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.o.uk