

# TECHNICAL DATA SHEET



**Product code:** 7933 **Sector:** Motorcycle, Scooter & ATV

**Issue No:** 3

**Issue Date:** 01/03/23

## Classic 2T

2 stroke oil for use in classic motorcycle and scooter applications.

### Description

A mineral 2 stroke engine oil, designed to work in classic applications where maximum lubricity and protection is required. The traditional technology used is ideal for the older air-cooled engines, and the low ash formulation prevents ring sticking, piston seizure and plug fouling.

### Application

Suitable for use in classic motorcycle and scooter applications where 2 stroke oil is required.

### Directions for use

If automatic lubrication system add to the designated tank. If self-mix then mix with petrol at the ratio recommended by the equipment manufacturer typically 40:1 up to 50:1.

### Performance Profile

API TC, TB, TA  
JASO FC, FB  
ISO-L-EGC

### Features & Benefits

- Low ash formulation.
- Reduced throttle sticking.
- Dyed 'blue' for easy recognition of the product and treated fuel.

### Typical Characteristics

Density @ 15°C, g/ml	0.892
Kinematic Viscosity @ 100°C, cSt	13.8
Flash Point, °C	230
Colour	Blue

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website  
[www.millersoils.co.uk](http://www.millersoils.co.uk)



**MADE IN BRITAIN**

**Millers Oils Ltd**  
Brighouse West Yorkshire HD6 3DP UK  
Tel: +44(0) 1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)