



SAFETY DATA SHEET
PERFORMANCE BRAKE FLUID DOT 5.1

Page: 1

Compilation date: 22/11/2016

Revision No: 1a

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PERFORMANCE BRAKE FLUID DOT 5.1

Product code: 7977

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Millers Oils Ltd
Hillside Oilworks
Rastrick Common
Brighouse
West Yorkshire
HD6 3DP
United Kingdom

Tel: +44 (0)1484 713201

Fax: +44 (0)1484 721263

Email: h.s@millersoils.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1484 713201

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: This product has no classification under CLP.

2.2. Label elements

Label elements: This product has no label elements.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

SAFETY DATA SHEET
PERFORMANCE BRAKE FLUID DOT 5.1

Page: 2

Hazardous ingredients:

2-[2-(2-BUTOXYETHOXY)ETHOXY]ETHANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
205-592-6	143-22-6	-	Eye Dam. 1: H318	1-10%

2,2'-OXYBISETHANOL - REACH registered number(s): 01-2119457857-21-XXXX

203-872-2	111-46-6	-	Acute Tox. 4: H302	1-10%
-----------	----------	---	--------------------	-------

DIETHYLENE GLYCOL MONOMETHYL ETHER

203-906-6	111-77-3	-	Repr. 2: H361d	1-10%
-----------	----------	---	----------------	-------

2-(2-BUTOXYETHOXY)ETHANOL

203-961-6	112-34-5	-	Eye Irrit. 2: H319	1-10%
-----------	----------	---	--------------------	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

[cont...]

SAFETY DATA SHEET
PERFORMANCE BRAKE FLUID DOT 5.1

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2,2'-OXYBISETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	101 mg/m ³	-	-	-

DIETHYLENE GLYCOL MONOMETHYL ETHER

EU	50,1 mg/m ³	-	-	-
----	------------------------	---	---	---

2-(2-BUTOXYETHOXY)ETHANOL

UK	67.5 mg/m ³	101.2 mg/m ³	-	-
----	------------------------	-------------------------	---	---

DNEL/PNEC Values

SAFETY DATA SHEET
PERFORMANCE BRAKE FLUID DOT 5.1

Page: 4

Hazardous ingredients:

2,2'-OXYBISETHANOL

Type	Exposure	Value	Population	Effect
DNEL	Dermal	43 mg/kg bw/day	Workers	-
DNEL	Dermal	21 mg/kg bw/day	Consumers	-

8.2. Exposure controls

Engineering measures: The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: colourless to amber

Odour: Bland

Evaporation rate: No data available.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: miscible in any ratio

Viscosity: No data available.

Boiling point/range°C: > 260

Melting point/range°C: < -50

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: >120

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: > 300

Vapour pressure: No data available.

Relative density: 1.030 - 1.090

pH: 7 - 11.5

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

[cont...]

SAFETY DATA SHEET
PERFORMANCE BRAKE FLUID DOT 5.1

Page: 5

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
DERMAL	RAT	LD50	> 2000	mg/kg
ORAL	RAT	LD50	> 5000	mg/kg

Hazardous ingredients:

2,2'-OXYBISETHANOL

DERMAL	RBT	LD50	13300	mg/kg
ORAL	RAT	LD50	19600	mg/kg

DIETHYLENE GLYCOL MONOMETHYL ETHER

IPR	RAT	LD50	2722	mg/kg
ORL	MUS	LD50	8222	mg/kg
ORL	RAT	LD50	4	ml/kg

2-(2-BUTOXYETHOXY)ETHANOL

ORL	MUS	LD50	6050	mg/kg
ORL	RAT	LD50	4500	mg/kg

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

[cont...]

SAFETY DATA SHEET
PERFORMANCE BRAKE FLUID DOT 5.1

Page: 6

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
RAINBOW TROUT (<i>Oncorhynchus mykiss</i>)	96H LC50	> 100	mg/l

Hazardous ingredients:

2,2'-OXYBISETHANOL

Daphnia magna	48H EC50	> 10000	mg/l
pimephales promelas	96H LC50	75200	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

[cont...]

SAFETY DATA SHEET
PERFORMANCE BRAKE FLUID DOT 5.1

Page: 7

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Conforms to regulation (EC) No 1907/2006 (REACH)

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H361d: Suspected of damaging the unborn child.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.