



PRODUCT DATA SHEET



Product No	5268
Issue No.	2
Issue Date	16/07/14

PRODUCT NAME/VISCOSITIES: BLACK ADHESIVE 0

DESCRIPTION:

An adhesive bitumen based EP (Extreme Pressure) lubricant for open gears.

APPLICATION:

Use as received, by means of brush or pump application. Store at a minimum temperature of 15°C for ease of application.

USER BENEFITS:

Black Adhesive 0 is an easy to apply adhesive grease and recommended for use on wire ropes, flexible couplings, gears and sliding surfaces of drag lines and shovels.

- Good adhesion to working surfaces.
- Good load carrying properties.
- Excellent water and corrosion resistance.

TYPICAL CHARACTERISTICS:

Appearance	Black Heavy Tacky Compound
Kinematic Viscosity @ 100°C	200cSt
Thickener	Bitumen
Base Oil Viscosity @100°C	100cSt
Pour Point °C	0
Flash Point °C	270
Operating Temperature Range °C	-15 to +80

HEALTH AND SAFETY:

Health and Safety Data Sheet 5268 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

