



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES:

CRX 75w110 NT+

Product No	7967
Issue No.	2
Issue Date	04/01/17

DESCRIPTION:

A competition heavy-duty fully synthetic transmission oil for highly stressed applications. A blend of synthetic base stocks and shear stable viscosity modifiers. Incorporates "Nano Technology" additive chemistry to significantly reduce internal frictional and power losses, combined with extreme pressure additives. For use in manual transmissions, synchromesh, non-synchromesh, sequential gearboxes, transfer gearboxes, transaxles and hypoid differentials. Competition grade transmission oils which are available in various viscosities and are formulated using a unique combination of improved chemistry and lower friction NANODRIVE additives to massively reduce friction vs a standard oil.

APPLICATION:

Designed for the lubrication of competition transmission systems which are subject to high stresses or arduous applications e.g. long distance racing on very high power and torque output. Manual transmissions, synchromesh, non-synchromesh, sequential gearboxes, transfer gearboxes, transaxles and hypoid differentials without limited slip which require API GL4 or GL5 performance.

Recommended for modern transmissions where full synthetic oil is specified, especially for high performance road and track day applications. Hewland, Xtrac, Glebe Transmissions, ZF, Tran X, Samsonas.

Note: Not suitable for plate type limited slip differentials, instead use CRX LS 75w140 NT+.

USER BENEFITS:

- Laboratory tests and results show up to a further 15% reduction in friction and up to a further 17% reduction in wear over the previous award winning NT range
- Exceptional cold flow properties for easier gear changes.
- Very good oxidation resistance and superior thermal stability.
- Low friction formulation to help reduce operating temperatures.
- High film strength for maximum component protection.
- Reduces friction and wear.
- Significantly reduces friction, temperature, wear and minimises power loss.
- Proven solution to gearbox problems in high performance rally cars.

PERFORMANCE PROFILE:

- API GL4
- ZF TE-ML-05B
- ZF TE-ML-17B
- API GL5
- ZF TE-ML-07A
- API MT-1
- ZF TE-ML-12B
- MIL-PRF-2105E
- ZF-TE-ML-16F

Millers Oils Ltd
 Brighouse, West Yorkshire
 HD6 3DP, UK
 Tel: +44(0)1484 713201
www.millersoils.co.uk



MILLERS OILS

**PRODUCT
DATA SHEET****TYPICAL CHARACTERISTICS:**

SAE Viscosity Grade	75w110
Specific Gravity @ 15°C	0.861
Kinematic Viscosity @40°C	132cSt
Kinematic Viscosity @ 100°C	19.5cSt
Brookfield Viscosity @ -40°C	136,000mPas
Viscosity Index	169

HEALTH AND SAFETY:

Health and Safety Data Sheet 7967 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk