



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES: **CSS 10w40**

Product No	7971
Issue No.	2
Issue Date	04/01/17

DESCRIPTION:

High performance competition semi-synthetic engine oil. Combination of the highest quality and latest performance additives in synthetic and mineral base stocks. CSS 10w40 is a high performance semi synthetic road and race oil for car and motorcycle engines alike.

APPLICATION:

As received for engine lubrication of high performance car or motorcycle engines.

USER BENEFITS:

- Provides up to a 26% reduction in friction plus a reduction in wear compared to a standard engine oil
- The latest lubricant technology has been utilised to provide a catalytic converter compatible oil, engineered to meet the demands of today's competition engines and conditions.
- Sophisticated performance additive package
- Semi-synthetic base fluid. Provides maximum engine protection and minimum power loss.
- Suited for modern high performance engines with or without turbo chargers

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	10w40
Specific Gravity @ 15°C	0.880
Kinematic Viscosity @ 100°C	14.0cSt
Kinematic Viscosity @ 40°C	96cSt
Viscosity Index	150
Pour Point °C	<-25
Flashpoint °C	>200
Cold Crank Viscosity @ -25°C	7,000cP max

HEALTH AND SAFETY:

Health and Safety Data Sheet 7951 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk