



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES: CHAIN LUBRICANT 1461

Product No	5325
Issue No.	3
Issue Date	17/11/20

DESCRIPTION:

High temperature chain lubricant with synthetic ester-based technology for outstanding thermal stability.

APPLICATION:

Use as received and apply by automatic lubrication equipment in accordance with manufacturer's instruction, or manually to the chain by brush.

USER BENEFITS:

- Wide operating temperature range, with maximum continuous operation up to 250°C with higher temperatures possible for intermittent use.
- High film strength to protect against wear for extended chain life.
- Very low volatility rate for minimised evaporation loss and fumes.
- High resistance to moisture and acid fumes for protection in even extreme environments.
- Ashless formulation for minimised deposit formation.

TYPICAL CHARACTERISTICS:

Characteristic	Typical value
Specific gravity @ 15°	0.978
Kinematic viscosity @ 100°C [cSt]	14.8
Kinematic viscosity @ 40°C [cSt]	152
Viscosity index	96
Pour point [°C]	-20
Flashpoint [°C]	>250
Volatility loss, 4 hours @ 250°C [%]	8
Part code	5325

HEALTH AND SAFETY:

Safety data sheets are available on request. When used for the purpose recommended and with due regard to the appropriate health and safety data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

