PRODUCT NAME/VISCOSITIES:

CLASSIC DIFFERENTIAL OIL 85w140 GL5

Product No	7930
Issue No.	2
Issue Date	26/02/19

DESCRIPTION:

An extreme pressure differential oil SAE 85w140 mineral based differential oil with performance additives. This product is for use in hypoid differentials requiring EP lubricants providing superior performance.

APPLICATION:

Use as received in Hypoid differentials requiring extreme pressure lubricants and GL5 specification.

USER BENEFITS:

- Provides performance level specified by manufacturers for axles and final drives.
- Viscosity profile selected to meet the 'classic vehicle' requirements.
- Low friction and reduced axle noise.
- Non aggressive to yellow metals.

PERFORMANCE PROFILE:

API GL5

TYPICAL CHARACTERISTICS:

SAE viscosity grade	85w140
Specific gravity at 15°C	0.908
Kinematic viscosity at 100°C	27.2cSt
Kinematic viscosity at 40°C	390cSt
Viscosity index	97
Pour point °C	-18
Flashpoint °C	200

HEALTH AND SAFETY:

Health and Safety Data Sheet 7930 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils technical department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

