



# PRODUCT DATA SHEET



## PRODUCT NAME/VISCOSITIES:

### CLASSIC GEAR OIL EP 140 GL4

Product No	7928
Issue No.	2
Issue Date	26/02/19

## DESCRIPTION:

An extreme pressure gear oil SAE 140 mineral based gear oil with performance additives. This product is engineered for gearboxes and differentials requiring EP lubricant to provide low friction and reduced noise.

## APPLICATION:

Use as received in classic gearboxes and differentials requiring extreme pressure (EP) lubricants and GL4 specification. Also suitable for brass and bronze components i.e. non stain.

## USER BENEFITS:

- Provides performance level specified by manufacturers for gearboxes and axles.
- Viscosity selected to meet classic vehicle requirements.
- Low friction and reduced noise.

## PERFORMANCE PROFILE:

Provides performance meeting or exceeding API GL4, MIL-L-2105.

## TYPICAL CHARACTERISTICS:

SAE viscosity grade	14
Specific gravity at 15°C	0.905
Kinematic viscosity at 100°C	31.0cSt
Kinematic viscosity at 40°C	484.3cSt
Viscosity index	94
Pour point °C	-9
Flashpoint °C	238

## HEALTH AND SAFETY:

Health and Safety Data Sheet 7928 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils technical department.

For Technical assistance call +44 (0) 1484 475060 or email [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)