



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES: Classic Pistoneeze 10w40

Product No	8144
Issue No.	1
Issue Date	14/08/2019

DESCRIPTION:

This product is a moderate detergent premium SAE 10w40 multigrade semi synthetic engine oil. High quality solvent refined base oils with latest technology performance additives and shear stable viscosity index improver. It is specifically engineered for classic cars incorporating modern filtration systems, and is formulated with ZDDP (zinc/phosphorus).

APPLICATION:

Use as received for engine lubrication for classic vehicles, both petrol and diesel, where a multigrade 10w40 is required.

USER BENEFITS:

- Incorporates modern additive technology with period viscometrics to provide the optimum lubrication characteristics.
- Suitable for higher mileage applications where oil consumption is a problem as high viscosity helps to reduce oil loss and leakage.
- The modern technology ensures an oil which will meet up to date specifications along with meeting the 'period' performance requirements.

PERFORMANCE PROFILE:

API SL/CF
ACEA A3/B4
MB 229.1

TYPICAL CHARACTERISTICS:

SAE viscosity grade	10w40
Specific gravity at 15°C	0.865
Kinematic viscosity at 100°C	13.0 cSt
Kinematic viscosity at 40°C	85.65 cSt
Viscosity index	149
Pour point °C	<-42
Flashpoint °C	>213
Cold crank viscosity	4500 cP

HEALTH AND SAFETY:

Health and Safety Data Sheet 8144 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils technical department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk