



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES: CLASSIC PISTONEEZE 40

Product No	7909
Issue No.	2
Issue Date	26/02/19

DESCRIPTION:

This product is a moderate detergent monograde mineral engine oil. It is specifically engineered for classic cars and is also suitable in vintage cars incorporating a modern filtration system. It is formulated with ZDDP (zinc/phosphorus).

APPLICATION:

Classic Pistoneeze 40 is suited to vintage vehicles where a monograde is required and the owner is confident that there is no dirt and debris collected in the crankcase. Also ideal for later vehicles built with superior oil filtration systems which were designed to run on monograde oils with detergent and dispersant additives.

USER BENEFITS:

This monograde oil gives good oil control and no loss of viscosity due to shear. Provides the level of wear protection and anti-oxidant protection required in classic vehicles.

PERFORMANCE PROFILE:

API SG, CD

TYPICAL CHARACTERISTICS:

SAE viscosity grade	4
Specific gravity at 15°C	0.900
Kinematic viscosity at 100°C	15cSt
Kinematic viscosity at 40°C	146
Viscosity index	104
Pour point °C	-30
Flashpoint °C	>200

HEALTH AND SAFETY:

Health and Safety Data Sheet 7909 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils technical department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk