



PRODUCT DATA SHEET



Product No	5298
Issue No.	2
Issue Date	17/03/10

PRODUCT NAME/VISCOSITIES:
DELTA 000EP

DESCRIPTION:

Lithium based semi-fluid grease with extreme pressure (EP)

APPLICATION:

Use as received for centralised lubrication systems requiring a semi-fluid grease.

USER BENEFITS:

- Adhesive properties.
- Good pumpability.
- Resistant to Water.
- High degree of corrosion protection.

TYPICAL CHARACTERISTICS:

Appearance	Dark Brown Smooth Semi-Fluid Grease
NLGI Classification	000
Thickener	Lithium Soap
Solid Lubricant	n/a
Base Oil	Mineral Oil
Base Oil Viscosity @40°C	180cSt
Worked Penetration (IP50)	445 to 475
Drop Point (IP132) °C	n/a
Copper Corrosion (IP112)	Pass
Emcor (IP 220) Corrosion Test	0 : 0
Four Ball Weld Load (IP239)	315kgs
Timken OK Load (IP326)	23kgs (50lbs)
Operating Temperature Range °C	-30 to +110

HEALTH AND SAFETY:

Health and Safety Data Sheet 5298 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
 Brighouse, West Yorkshire
 HD6 3DP, UK
 Tel: +44(0)1484 713201
www.millersoils.co.uk