



PRODUCT DATA SHEET



Product No	5317
Issue No.	2
Issue Date	17/03/10

PRODUCT NAME/VISCOSITIES: **DELTA 00EP**

DESCRIPTION:

Lithium based semi-fluid grease with extreme pressure(EP) additives.

APPLICATION:

Use as received for centralised lubrication systems and gearboxes requiring a semi-fluid grease.

USER BENEFITS:

- Self collapsing, will not channel.
- Resistant to water.
- High degree of corrosion protection.

TYPICAL CHARACTERISTICS:

Appearance	Dark Brown Semi-Fluid Grease
NLGI Classification	00
Thickener	Lithium Soap
Solid Lubricant	n/a
Base Oil	Mineral Oil
Base Oil Viscosity @40°C	180cSt
Worked Penetration (IP50)	400 to 430
Drop Point (IP132) °C	n/a
Copper Corrosion (IP112)	Pass
Emcor (IP 220) Corrosion Test	0 : 0
Four Ball Weld Load (IP239)	315kgs
Timken OK Load (IP326)	23kgs (50lbs)
Operating Temperature Range °C	-30 to +110

HEALTH AND SAFETY:

Health and Safety Data Sheet 5317 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

