



PRODUCT DATA SHEET



Product No	5269
Issue No.	2
Issue Date	17/03/10

PRODUCT NAME/VISCOSITIES: **DELTA 0EP**

DESCRIPTION:

Lithium based semi-fluid grease with extreme pressure (EP) additives.

APPLICATION:

Use as received for centralised lubrication systems and gearboxes requiring a semi-fluid grease.

USER BENEFITS:

- Self collapsing will not channel.
- Good pumpability
- Reduces leakage in poorly sealed equipment.
- High degree of corrosion protection.

TYPICAL CHARACTERISTICS:

Appearance	Dark Brown Smooth Semi-Fluid Grease
NLGI Classification	0
Thickener	Lithium Soap
Solid Lubricant	n/a
Base Oil	Mineral Oil
Base Oil Viscosity @40°C	180cSt
Worked Penetration (IP50)	355 to 385
Drop Point (IP132) °C	n/a
Copper Corrosion (IP112)	Pass
Emcor (IP 220) Corrosion Test	0 : 0
Four Ball Weld Load (IP239)	315kgs
Timken OK Load (IP326)	23kgs (50lbs)
Operating Temperature Range °C	-30 to +110

HEALTH AND SAFETY:

Health and Safety Data Sheet 5269 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk