



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES:

DEWATERING FLUID 1782

| | |
|------------|---------|
| Product No | 5406 |
| Issue No. | 2 |
| Issue Date | 14/5/15 |

DESCRIPTION:

A water displacing grade that contains anti-corrosion additives and lubricant properties.

APPLICATION:

Due to its low viscosity the grade can be applied by brush dip or spray.

USER BENEFITS:

- Readily displaces water.
- Excellent penetrative action.
- Lubricant and corrosion protection properties.
- Suitable for refillable spray.
- Economical in use.
- Effective penetrating fluid.
- Free from silicone type materials.

TYPICAL CHARACTERISTICS:

| | |
|----------------------------|------------------------------|
| Specific Gravity @ 15°C | 0.799 |
| Kinematic Viscosity @ 40°C | 2.0cSt |
| Flashpoint °C | 40 |
| Nominal Film Thickness | 1.27 µm |
| Coverage | 109.07 m ² /litre |
| Indoor Protection | up to 3 months |

HEALTH AND SAFETY:

Health and Safety Data Sheet 5406 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

