



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES: EROSOL 3D

Product No	5122
Issue No.	2
Issue Date	24/06/10

DESCRIPTION:

Light hydrocarbon fraction.

APPLICATION:

Use as received as a dielectric fluid in spark erosion machines.

USER BENEFITS:

Erosol 3D has been developed to provide:-

- Good cooling properties
- Good profile sharpness
- A relatively high flash point to minimise Health & Safety considerations
- Long service life especially if correctly filtered

PERFORMANCE PROFILE:

- Erosol 3D has found numerous satisfied customers using various types of equipment. However, the machine manufacturers specifications should be checked before its use.

TYPICAL CHARACTERISTICS:

Density @ 15°C	0.818
Viscosity @ 40°C	3.8cSt
Pour Point °C	-9
Closed Flash Point °C	122

HEALTH AND SAFETY:

Health and Safety Data Sheet 5122 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk