

PRODUCT NAME/VISCOSITIES:**Ginetta Tech by Millers Oils 75w90**DATA SHEET NO: 8108
DT: 04/01/17**DESCRIPTION:**

Fully synthetic competition transmission oil that protects the gear teeth at low start up and high running temperatures. This transmission oil includes a triple ester formulation that works synergistically for optimised film strength and anti wear protection.

APPLICATION:

Designed for use in the Ginetta G40 axel and G40 and G55 gear boxes

Note: Not suitable for plate type limited slip differentials, instead use Ginetta Tech by Millers Oils LS 75w 90

USER BENEFITS:

- Exceptional cold flow properties for easier gear changes.
- Fast lubrication flow to component extremes on start up.
- Very good oxidation resistance and superior thermal stability.
- Low friction/low drag formulation to help reduce operating temperatures.
- High film strength for maximum component protection.
- Significantly reduces friction, temperature, wear and minimises power loss.

PERFORMANCE PROFILE:

- | | | | |
|----------------|--------------|--------------|---------------|
| • API GL4 | API GL5 | API MT-1 | MIL-PRF-2105E |
| • ZF TE-ML-02B | ZF TE-ML-05B | ZF TE-ML-07A | ZF TE-ML-12B |
| • ZF TE-ML-16F | ZF TE-ML-17B | ZF TE-ML-19C | ZF TE-ML-21B |

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	75w90
Specific Gravity @ 15°C	0.864
Kinematic Viscosity @40°C	89.0 cSt
Kinematic Viscosity @100°C	14.8 cSt
Brookfield Viscosity @ -40°C	52,000 mPas
Viscosity Index	175

HEALTH AND SAFETY:

Health and Safety Data Sheet 8108 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP UK
Tel: +44(0)1484 713201
Visit: millersoils.co.uk



Ginetta
Helios 47, Isabella Road,
Garforth, Leeds, LS25 2DY
Tel: 0113 385 4160
Visit: ginetta.com