



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES:

HYPOID 90 GL5

DATA SHEET NO: 5016

LM: 17/07/14

DESCRIPTION:

High performance extreme pressure (EP) Lubricant made from high quality solvent refined base stock with performance additives.

APPLICATION:

Use as received in manual transmissions and hypoid axles requiring extreme pressure lubricants including vehicle and industrial applications with hypoid gears.

USER BENEFITS:

- Wide choice of viscosities to suit applications
- Well proven superior performance
- Provides 'trouble free' operation
- Imparts exceptional load carrying ability
- Friction modified for mild limited-slip applications

PERFORMANCE PROFILE:

Provides performance meeting or exceeding:

- API GL-5
- MAN M342M-2 (160,000 km Drain)
- ZF TE-ML 05A, 7A, 12E, 16B, C, D, 17B, 19B
- MIL-L-2105D
- OEM performance levels for final drives

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	90
Specific Gravity @ 15°C	0.901
Kinematic Viscosity @ 100°C	19.0cSt
Kinematic Viscosity @ 40°C	216.0cSt
Viscosity Index	99
Pour Point °C	-18
Flashpoint °C	200



Millers Oils Ltd
 Brighouse, West Yorkshire
 HD6 3DP, UK
 Tel: +44(0)1484 713201
www.millersoils.co.uk

COMMERCIAL



PRODUCT DATA SHEET



HEALTH AND SAFETY:

Health and Safety Data Sheet 5016 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk