



# PRODUCT DATA SHEET



## PRODUCT NAME/VISCOSITIES:

**KR2T**

Product No	7960
Issue No.	2
Issue Date	18/10/17

## DESCRIPTION:

KR2T is a unique SAE 40 formulation, 2-stroke oil with a high performance/low ash profile.

Specifically developed for high revving 2 stroke engines.

Tested and proven in Rotax Max and Honda TM kart engines. Suitable for bikes, karts and all 2 strokes.

Homologated for use in CIK-FIA competitions and events.

## APPLICATION:

By mixing with petrol in the ratio recommended by the engine manufacturer, for use where maximum performance is required. (Typically between 40:1 and 50:1 should give best results).

## USER BENEFITS:

- Unique formulation improves sealing of the bores for increased power and torque.
- Burns cleanly for improved throttle response.
- Maximum lubricity for reduced wear.
- Prevents sticking throttle.
- Eliminates crank case deposits, making engine rebuilds easier.
- Suitable for all high performance air/ water cooled 2 stroke engines.
- Can be used in outboard engines not requiring ashless oils.
- Dyed blue for easy confirmation fuel has been treated.

## PERFORMANCE PROFILE:

- JASO FC
- API TC
- Global GC
- TISI

## TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	40
Specific Gravity @ 15°C	0.887
Flashpoint °C	>200

## HEALTH AND SAFETY:

Health and Safety Data Sheet 7960 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.