



# PRODUCT DATA SHEET



## PRODUCT NAME/VISCOSITIES:

### MAXIFLEET 15w40

DATA SHEET NO: 5740

LM: 01/2/19

#### DESCRIPTION:

A high performance engine oil designed for both diesel and petrol engines where compliance with the latest Euro 3 specification for emission controlled engines is not required.

#### APPLICATION:

Ideal for use in trucks, light commercial vehicles, vans and passenger cars including off-highway vehicles such as contractors' plant where the specification meets their requirements.

#### FEATURES AND BENEFITS:

- Maxifleet 15w40 is formulated using high quality mineral base oils, high performance viscosity index improvers and performance additive chemistry providing high levels of detergency and dispersancy to ensure engine cleanliness.
- By careful selection of a suitable viscosity, oil consumption can be kept to an absolute minimum also providing a buffer against possible fuel dilution.
- Oil drain periods are kept to standard recommendations.
- Maxifleet 15w40 is recommended where there is a wide variety of diesel and petrol engines not requiring the latest lubricant specifications and where a true 'work-horse' is required to provide maximum lubrication capability.

#### SPECIFICATIONS

- E2 (Issue 5) B3 / A2
- API CI-4, SJ MB 228.1
- MAN M271 MTU Type 1
- Volvo VDS Mack EO-L Plus

#### TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	15w40
Specific Gravity @ 15°C	0.882
Kinematic Viscosity @ 100°C	13.6cSt
Kinematic Viscosity @ 40°C	96cSt
Viscosity Index	142
Pour Point °C	<-20
Flashpoint °C	>200
Cold Crank Viscosity @ -20°C	7,000cP max
TBN mg KOH / gm	8.1
Sulphated Ash	1.04



**Millers Oils Ltd**  
 Brighouse, West Yorkshire  
 HD6 3DP, UK  
 Tel: +44(0)1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)



# PRODUCT DATA SHEET



## STORAGE:

All packages should be stored indoors at ambient temperatures in a well ventilated area. Keep containers tightly closed when not in use. Where storing outside is unavoidable, barrels should be laid horizontally to avoid water ingress and to protect the product labelling and marking. Clean up any spilled material immediately. Take all necessary precautions against accidental spillage into soil or water.

## HEALTH AND SAFETY AND ENVIRONMENT:

Health and Safety and Environmental information is provided for this product in Millers Material Safety Data Sheet 5740. This gives details of any potential hazards, necessary precautions, first aid measures, environmental effects and disposal procedures.

All information relates only to the specific products designated herewith and may not be valid for this material if used in conjunction with any other materials or in any other process.

For Technical assistance call +44 (0) 1484 475060 or email [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)



**Millers Oils Ltd**  
Brighouse, West Yorkshire  
HD6 3DP, UK  
Tel: +44(0)1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)