



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES:

MILLERCARE AF (formerly) ANTIFOAM 2048 AM

Product No	5497
Issue No.	2
Issue Date	17/03/14

DESCRIPTION:

A blend of surface active polymers for use in water soluble metalworking fluids and associated industrial fluids.

APPLICATION:

Use as received as a tank side treatment between 0.01% and 0.02% depending on severity of foam. The antifoam should be added to the slow moving areas of the coolant system. Add the required antifoam and allow system to respond to the addition before adding any more.

Over dosing with antifoam can be counter productive, so little and often is the preferred method.

USER BENEFITS:

- Good foam control at low dilution rates.
- Low residue formation
- Non-silicone, no adverse effect on finishing process.

TYPICAL CHARACTERISTICS:

Specific Gravity @ 20°C	1.00
Solubility in Water	Dispersible
Appearance	Off White liquid

HEALTH AND SAFETY:

Health and Safety Data Sheet 5497 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

