TECHNICAL DATA SHEET





Product code: see below table Sector: Industrial Issue No: 3 Issue Date: 16/01/23

Food Grade

MILLFOOD GEAR OIL

Food grade, fully synthetic gear oil with anti-wear, corrosion protection and demulsification properties.

Application

Ideal for the lubrication of gearboxes in the food, drink, pharmaceutical and processing, packaging industries requiring food grade products.

Features & Benefits

- High viscosity index provides consistent performance over a wide temperature range and results
- In extended service intervals.
- Tackiness additives ensure oil protects gear surfaces, even on start up.
- Demulsification properties ensure quick separation of water from oil.
- All ingredients are FDA listed; Millfood Gear Oil is NSF H1 registered.
- Contains no genetically modified ingredients and does not contain any nut oil or derivatives.

Typical Characteristics

Millfood Gear Oil		150	320
Appearance		Clear adhesive fluid	
Base Fluid		Blend of synthetic oils	
Specific Gravity @ 15°C		0.870	0.870
Kinematic Viscosity @ 40°C		150 cSt	320 cSt
Pour Point (°C)		-36	-30
Flash Point (°C)		>250	>260
Temperature Range (°C)		-30 to +200	-30 to +240
Demulsibility (ASTM D1401) 30 min		40-40-0	40-40-0
Foaming (ASTM D892)	After Settling Sequence 1	Nil	Nil
	After Settling Sequence 2	Nil	Nil
After Settling Sequence 3		Nil	Nil
Copper Corrosion (ASTM D130)		1b	1b
FZG Gear Test Stage		12	12
Evaporation Loss 6.5 hrs @ 250°C, % Mass		5.0	4.0
NSF Registration Number		125901	125902
Product Code		5679	5680











TECHNICAL DATA SHEET





Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk







