

TECHNICAL DATA SHEET



Product code: 5446

Sector: Industrial

Issue No: 3

Issue Date: 04/05/22

MILLGAS 40

High quality solvent refined mineral oils with high performance additive package.

Application

Use as received for the lubrication of natural gas powered engines according to the OEM requirements and specification.

Features & Benefits

- Good oxidation stability for maintained performance.
- Suitable for high temperature operation.
- Contains anti-wear and detergent/dispersant additives.

Performance Profile

- API CG-4

Typical Characteristics

| | |
|-----------------------------|---------------|
| SAE Viscosity Grade | 40 |
| Specific Gravity @ 15°C | 0.90 |
| Kinematic Viscosity @ 100°C | 14.5cSt |
| Kinematic Viscosity @ 40°C | 141.6cSt |
| Viscosity Index | 101 |
| Flashpoint °C | 220 |
| Sulphated Ash | 1.08% |
| TBN | 8.1 mg KOH/gm |

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk



MADE IN BRITAIN

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.co.uk