



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES:

MULTIFLEET 15W-40

DATA SHEET NO: 5752
LM: 17/04/19

DESCRIPTION:

Multifleet 15W-40 provides excellent protection for a range of Euro III and some Euro IV and Euro V vehicles and US technology vehicles. Also suitable for use in petrol engines requiring the API SL specification.

APPLICATION:

Recommended for use in diesel engines requiring a lubricant with the performance profile ACEA E7, API CI-4,

MB 228.3 and Volvo VDS-3. Formulated for use in diesel engines fitted to trucks, light commercial vehicles, vans and off-highway equipment.

Multifleet 15W-40, also complies to API SL specification and can therefore be recommended for use in petrol engines. A true mixed fleet lubricant which can be used where one oil is preferred for simplicity and inventory reasons.

FEATURES AND BENEFITS:

- The mineral oil 15W-40 formulation offers a high degree of engine protection and excellent oil consumption control.
- Whilst standard oil drain periods are recommended, the high levels of detergency and dispersancy ensure engine cleanliness and a reassuring performance margin at the end of the stipulated drain intervals.
- For fleet operation where diesel engines form the major part of the fleet but where it is advantageous to use the same oil in petrol engines.

SPECIFICATIONS:

- | | |
|---|---|
| <ul style="list-style-type: none"> • ACEA E7 • API CI-4, SL • MB 228.3 • Volvo VDS-3 • CAT ECF-2, ECF-1a • Deutz DQC III-10 • Global DHD-1 | <ul style="list-style-type: none"> • Detroit Diesel DDC 93K215 • MTU Type 2 • Renault RLD-2 • MAN M3275 • Mack EO-N EO-M Plus • Cummins 20076, 20077, 20078 |
|---|---|



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk



PRODUCT DATA SHEET



TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	15W-40
Specific Gravity @ 15°C	0.88
Kinematic Viscosity @ 100°C	13.75cSt
Kinematic Viscosity @ 40°C	97.82cSt
Viscosity Index	141
Pour Point °C	<-20
Flashpoint °C	>200
Cold Crank Viscosity @ -20°C	7,000cP max
TBN mg KOH / gm	10.4
Sulphated ash	1.39

STORAGE:

All packages should be stored indoors at ambient temperatures in a well ventilated area. Keep containers tightly closed when not in use. Where storing outside is unavoidable, barrels should be laid horizontally to avoid water ingress and to protect the product labelling and marking. Clean up any spilled material immediately. Take all necessary precautions against accidental spillage into soil or water.

HEALTH AND SAFETY AND ENVIRONMENT:

Health and Safety and Environmental information is provided for this product in Millers Oils Material Safety Data Sheet 5752. This gives details of any potential hazards, necessary precautions, first aid measures, environmental effects and disposal procedures.

All information relates only to the specific products designated herewith and may not be valid for this material if used in conjunction with any other materials or in any other process.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk